


Typical Section 4



Typical Section 3

NOTES

1. Failed Pavement Areas

- excavate existing pavement down to 100mm depth or as required
- lay, cement stabilise and compact basecourse up to existing pavement level
- lay, form to grade and compact 100mm thick basecourse
- apply a membrane seal coat to finished basecourse level using 12mm chip seal followed by 5mm chip seal
- apply 40mm thick hotmix wearing course and taper from 40mm to 20mm on shoulders

2. Normal Pavement Areas

- lay, form to grade and compact 100mm thick basecourse
- apply membrane seal coat to finished basecourse level using 12mm chip seal followed by 5mm chip seal
- apply 40mm thick hotmix wearing course and taper from 40mm to 20mm on shoulders

REVISION		BY/APPD	DATE/NOTES	TECHNICAL SERVICES DIVISION		PROJECT TITLE		DESIGNED:	DATE:	CHECKED:	DATE:
1. Drawings revised due to design adjustment		T.M	Dec'11	1. These drawings & designs are copyright and are not to be reproduced without the written consent of the Designer		Rarotonga Road Network Improvements		T. Mana	April 2014		April 2014
				2. Verify all dimensions & levels on the site prior to commencing work							
				3. All discrepancies to be referred to the design office for clarification							
				4. All dimensions in millimetres unless otherwise shown							