



NOTES

1. Footpath Repairs
 - dig out where required
 - place and compact 100mm thick backfill
 - place and broom finish 100mm thick 25MPa concrete
2. Carriageway
 - excavate existing pavement at failed areas down to 100mm deep or as required
 - lay and cement stabilise 100mm thick basecourse
 - apply a membrane seal coat to finished basecourse level using 12mm chip seal followed by 5mm chip seal
 - apply 40mm thick hotmix wearing course and taper from 40mm to 20mm on edges to match road side drains




Typical Section 2



Typical Section 1

REVISION		BY	APP'D	DATE	NOTES	
1.	Drawings revised due to design adjustment	TM		Dec'11	1	These drawings & designs are copyright and are not to be reproduced without the written consent of the Designer
					2	Verify all dimensions & levels on the site prior to commencing work
					3	All discrepancies to be referred to the design office for clarification
					4	All dimensions in millimetres unless otherwise shown

TECHNICAL SERVICES DIVISION		PROJECT TITLE	
 <div>Infrastructure Cook Islands</div> <div>Box 102 Avarua District P.O. Box 20521 P.O. Box 24321 Web: www.icig.gov.ck</div>		Rarotonga Road Network Improvements	
DRAWING TITLE		TYPICAL SECTIONS 1	

DESIGNED:	T. Mana	DATE:	April 2014	CHECKED:		DATE:	April 2014
DRAWN:	T. Mana	DATE:	April 2014	APPROVED:	Secretary, ICI	DATE:	April 2014
CLIENT NAME:		SCALES:	H 1:50 V 1:10	DWG No.	CI13-13.2	SHT No.	33 of 37